

Portable Aviation Ground Light PLB 500



Compliance

- ICAO (Annex 14, Vol.1 Par 5.3.2)
- CAP168 (Table 6A.1)

The PLB500 portable light has been designed to be compact and robust, with weight kept to a minimum to facilitate easy handling during transportation and installation

The PLB500 portable light is easily charged by simply plugging the charger into the socket located on the top section of the housing.

Five, Ten & 25 way charging units are available.

Also available is a storage trailer for easy deployment and charging of the PLB500.

Features

- Housing is a two-part moulded, high strength, flameretardant polycarbonate
- Re-chargeable battery. A battery indicator gives early warning of the batteries condition
- The lead acid 12 AH battery provides a minimum of 16 hours of continuous operation between charges.
- Durable high strength lens
- Omni directional beam spread
- Fast and easy lamp changing through a twist lock action holder
- An internal switch allows the selection of either a constant or flashing illumination.
- Optional photo-electric sensor for automatic switching during low light conditions is included as standard
- Should high winds or jet be a problem the unit can be held down by a dual bolt fixing

Specification

- The PLB500 is available with a choice of lens colours (Amber, Red, Green, Blue and Clear)
- Photo-electric sensor for automatic switching during low light conditions
- Long Life Filament Lamp,
- 12 A/Hour Lead Acid Battery
- Selectable Flash option
- Integral Carrying handle

