

# Halogen lamps, current-controlled, single-ended

### Areas of application

- Airfield lighting



# Product family benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

## Product family features

- Dimmable
- Infrared radiation output that provides light in the worst of conditions





# Product family datasheet

## Technical data

	Product informatio n	Electrical data		Photomet rical data	Dimensions & weight		
Product description	Order reference	Lamp current	Nominal wattage	Nominal luminous flux	Diameter	Length	Light center length (LCL)
64322	64322 30W GY9.5	6.6 A	30.00 W	400 lm	13.5 mm	44.5 mm	25.4 mm
64311	64311 36W G6.35	6.0 A	36.00 W		11.0 mm	47.0 mm	33.0 mm
64321	64321 45W G6.35	6.6 A	45.00 W	900 lm	11.5 mm	47.0 mm	33.0 mm
64320	64320 45W GZ9.5	6.6 A	45.00 W	875 lm	11.5 mm	44.5 mm	25.4 mm
64346	64346 100W 6,6A	6.6 A	100.00 W		13.5 mm	47.0 mm	33.0 mm
64386	64386 200W G6.3	6.6 A	200.00 W	4700 lm	13.5 mm	47.0 mm	33.0 mm
58750	58750 200W GY9.	6.6 A	200.00 W	5200 lm	13.0 mm	65.0 mm	39.1 mm
64354	64354 150W GY9.	6.6 A	150.00 W		13.5 mm	65.0 mm	39.1 mm

	Lifespan	Additional product data	Capabilities	Country specific categorizations	
Product description	Lifespan	Base (standard designation)	Burning position	ANSI code	LIF
64322	1500 h	GY9.5	s90 <sup>1)</sup>	EXL	
64311	1500 h	G6.35	s90		J1/59
64321	1500 h	G6.35	s90		J1/57
64320	1500 h	GZ9.5	s90	EXM	
64346	1200 h	G6.35	s90		J1/58
64386	1500 h	G6.35	s90		J1/39
58750	1300 h	GY9.5	Any	EZL	
64354	1500 h	GY9.5	s90	EWR	

 $<sup>^{1)}</sup>$  Despite transverse filament, can be inclined at any angle in s90 position

## Product family datasheet

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### References / Links

For more information on airfield lamps see the brochure:

"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.